

APP CRS

Rwy Idg

4002

TDZE

631

Apt Elev

632

RNAV (GPS) RWY 6

HEBER SPRINGS MUNI (HBZ)

RNP APCH.

NA

Procedure NA at night. Rwy 6 helicopter visibility reduction below 1 SM NA. Obtain local altimeter setting on CTAF; when not received, use Batesville altimeter setting and increase all MDAs 80 feet, and increase LNAV visibility Cat C and D ¼ SM. Increase Circling visibility Cat C ¼ SM, Cat D ½ SM.


MISSED APPROACH: Climb to 4000 direct POYOG and hold, continue climb-in hold 4000.

MEMPHIS CENTER

126.85 281.55

UNICOM

122.7 (CTAF) 0



ELEV 632

TDZE 631

4000 POYOG

4 NM Holding Pattern

RILVE

JEKMU

RW06

6000 4000

239° 059°

059°

2600

060°

3.00°

TCH 36

5.9 NM

6.1 NM

CATEGORY

A

B

C

D

LNAV MDA

1240-1

609 (700-1)

1240-1¾

609 (700-1¾)

CIRCLING

1240-1

1380-1

1380-2¼

1440-2½

608 (700-1)

748 (800-1)

748 (800-2¼)

808 (900-2½)

MIRL Rwy 6-24 0

REIL Rlys 6 and 24 0