

APP CRS
188°

Rwy Ldg
TDZE
Apt Elev

3501
1204
1207

RNAV (GPS) RWY 19

ASHLAND COUNTY (3G4)

RNP APCH.

▼

▲ NA

Rwy 19 helicopter visibility reduction below 1 SM NA.
Procedure NA at night. Use Mansfield altimeter setting,
when not received use Wooster altimeter setting.

MFD ASOS
125.3

CLEVELAND APP CON ★
128.35 360.65

UNICOM
122.7 (CTAF) 0

The diagram illustrates the RNAV (GPS) RWY 19 approach. The primary route starts at ECZIF (3000) and proceeds south to JUKAP (2800), then to RWY 19 (1299±). A holding pattern is established at ECZIF (3000) with a 188° heading. A missed approach procedure is shown as a climb to 3000, a left turn on track 098°, and a hold at READS. The chart also shows a 30 NM holding pattern for ECZIF (3000) and a 30 NM holding pattern for JUKAP (2800). Key altitudes and distances are marked along the route.

ELEV 1207

TDZE 1204

188°

61

0.5% UP

3501 X 7.5

1

3000

HINPO

tr 098°

READS

VGSI and descent angles not coincident
(VGSI Angle 3.00/TCH 20).

4 NM Holding Pattern

JUKAP

3.04° TCH 40

188°

2800

008°

188°

3000

CATEGORY

A

B

C

D

LNAV MDA

1600-1

396 (400-1)

1600-1 1/8
396 (400-1 1/8)

NA

CIRCLING

1660-1

453 (500-1)

1740-1 1/2
533 (600-1 1/2)

NA

ASHLAND, OHIO

Orig-F 09SEP21

40°54'N-82°15'W

ASHLAND COUNTY (3G4)

RNAV (GPS) RWY 19