



WAAS CH 58332 W19A	APP CRS 186°	Rwy Idg TDZE 522 Apt Elev 522
--	------------------------	---

RNAV (GPS) RWY 19
MAYFIELD GRAVES COUNTY (M25)

RNP APCH - GPS. Circling Rwy 1 NA at night. Rwy 19 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using Paducah altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Paducah altimeter setting: increase LPV DA to 833 feet, LNAV/VNAV DA to 977 feet and all visibilities ¼ SM; increase all MDAs 80 feet and visibility Cats C and D ¼ SM.	MISSED APPROACH: Climb to 2300 direct LUXON and hold.
--	--

AWOS-3 120.625	MEMPHIS CENTER 133.65 292.15	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



2300	LUXON	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 35).	6 NM Holding Pattern
YOPKU 1.4 NM to RW19	CITBY 2400	JOELY	
RW19	1020	2400	006° → 6000 ← 186° 2400 GP 3.00° TCH 56
1.4 NM	4.3 NM	6.9 NM	
CATEGORY	A	B	C
LPV DA	772-1	250 (300-1)	
LNAV/VNAV DA	916-1½	394 (400-1½)	
LNAV MDA	880-1	358 (400-1)	
CIRCLING	1060-1 538 (600-1)	1060-1½ 538 (600-1½)	1280-2½ 758 (800-2½)

SE-1, 25 DEC 2025 to 22 JAN 2026

SE-1, 25 DEC 2025 to 22 JAN 2026