

LOC I-MQJ
108.7

APP CRS
252°

Rwy Ldg
TDZE **860**
Apt Elev **862**

ILS or LOC RWY 25
INDIANAPOLIS RGNL (MQJ)

When local altimeter setting not received, use Indianapolis Intl altimeter setting and increase all DA 55 feet and all MDA 60 feet, increase S-LOC 25 Cats C/D visibility ½ mile and Circling Cat D visibility ¼ mile.

NA

MALSR

MISSED APPROACH: Climb to 1400 then climbing left turn to 2400 on SHB VOR/DME R-334 to SHB VOR/DME and hold.

AWOS-3PT
124.175

INDIANAPOLIS APP CON
127.15 317.8

UNICOM
122.975 (CTAF)

ELEV 862 TDZE 860

1400 2400 SHB

SHB R-334

One Minute Holding Pattern

ELYSE LOM/INT 2660

072° 252° 2700

GS 3.00° TCH 53

5.4 NM

CATEGORY	A	B	C	D
S-ILS 25	1060-½ 200 (200-½)			
S-LOC 25	1220-½	360 (400-½)	1220-⅝ 360 (400-⅝)	
CIRCLING	1340-1	478 (500-1)	1360-1½ 498 (500-1½)	1660-2½ 798 (800-2½)

REIL Rwy 7 and 34

HIRL Rwy 7-25

MIRL Rwy 16-34

FAF to MAP 5.4 NM

Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48

INDIANAPOLIS, INDIANA

Amdt 3 17AUG17

39°51'N-85°54'W

INDIANAPOLIS RGNL (MQJ)

ILS or LOC RWY 25