

WAAS
CH **57927**
W12A

APP CRS
118°

Rwy Ldg
TDZE **2609**
Apt Elev **2615**

RNAV (GPS) RWY 12

ROY HURD MEML (E01)

▼

When local altimeter setting not received, use INK altimeter setting and increase all MDAs 80 feet and LNAV visibility Cat C ¾ SM, and LP visibility Cat C ½ SM, and

▲

Circling visibility Cat C ½ SM. Rwy 12 helicopter visibility reduction below 1 SM NA. Straight-in Rwy 12 NA at night, Circling Rwy 1, 12, 19 NA at night.

MISSED APPROACH: Climb to 3200 then climbing left turn to 6000 direct INK VORTAC and hold.

AWOS-3PT 118.225	FORT WORTH CENTER 133.1 298.95	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 24).

3200

6000

INK

POMVE

5000

118°

EGOJO

4000

3.00°

TCH 45

RWY 12

6.4 NM

4.2 NM

CATEGORY	A	B	C	D
LP MDA	3100-1	491 (500-1)	3100-1⅜ 491 (500-1⅜)	NA
LNAV MDA	3120-1	511 (600-1)	3120-1⅜ 511 (600-1⅜)	NA
CIRCLING	3280-1	665 (700-1)	3280-1¾ 665 (700-1¾)	NA

ELEV 2615

TDZE 2609

118°

61

4268 X 75

2972 X 75

30

MIRL Rwy 1-19 and 12-30 0

MONAHANS, TEXAS

Orig-B 12JUN25

31°35' N-102°55' W

ROY HURD MEML (E01)

RNAV (GPS) RWY 12