

WAAS
CH **81923**
W18A

APP CRS
174°

Rwy Ldg **5001**
TDZE **1177**
Apt Elev **1193**

RNAV (GPS) RWY 18

SUNDANCE (HSD)

RNP APCH - GPS.


▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Baro-VNAV and VDP NA when using PWA altimeter setting.

MISSED APPROACH:
Climb to 3200 direct
NUFAD and hold.

AWOS-3 120.975	OKE CITY APP CON 124.6 266.8	CLNC DEL 123.7	UNICOM 122.7 (CTAF) 0
--------------------------	--	--------------------------	---------------------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 30).		3200	NUFAD
3600		174°		174°	
GP 3.00°		TCH 40		2800	1720
7.1 NM		3.4 NM		0.6	1.1
CATEGORY	A	B	C	D	
LPV DA	1427-1	250 (300-1)		NA	
LNAV/VNAV DA	1473-1½	296 (300-1½)		NA	
LNAV MDA	1540-1	363 (400-1)	1540-1½ 363 (400-1½)	NA	
CIRCLING	1740-1 547 (600-1)	1840-1 647 (700-1)	1840-1¾ 647 (700-1¾)	NA	

MIRL Rwy 18-36 0