

WAAS CH 53608 W17A	APP CRS 173°	Rwy Idg 4605 TDZE 1827 Apt Elev 1827
--	------------------------	---

RNAV (GPS) RWY 17

CURTIS FLD (BBD)


RNP APCH - GPS.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C.
Baro-VNAV and VDP NA when using JCT altimeter setting. When local altimeter setting not received, use JCT altimeter setting: increase LPV DA to 2144 feet; increase LNAV/VNAV DA to 2194 feet; increase all MDAs 120 feet and LNAV visibility Cat C ¾ SM.

MISSED APPROACH: Climb to 4000 direct JENEV and hold.

AWOS-3 118.375	HOUSTON CENTER 132.35 317.5	UNICOM 122.8 (CTAF) 0
--------------------------	---------------------------------------	---------------------------------



4 NM Holding Pattern		ELAME		EYEDU		RAVLE 2.1 NM to RW17		0.9 NM to RW17		RW17		4000 ↑ JENEV ✧	
6000 ← 353°				3500		2540							
4000 → 173°													
GP 3.00° TCH 40				3500		2540							
		6 NM		3 NM		1.2 NM		0.9					
CATEGORY		A		B		C				D			
LPV DA		2027-1		200 (200-1)								NA	
LNAV/ VNAV		DA		2077-1		250 (300-1)						NA	
LNAV MDA		2160-1		333 (400-1)								NA	

