

WAAS
CH **93515**
W36A

APP CRS
002°

Rwy ldg **3513**
TDZE **73**
Apt Elev **74**

RNAV (GPS) RWY 36

HOLK FLD AT FOLEY MUNI (5R4)

RNP APCH - GPS

NA

Procedure NA at night. Rwy 36 helicopter visibility reduction below 1 SM NA. Use Fairhope altimeter setting. When not received, use Gulf Shores altimeter setting and increase all MDA 20 feet; increase LP and LNAV Cat C visibility 1/8 SM and Circling Cat C visibility 1/4 SM.


MISSED APPROACH:

Climb to 3100 direct RUPQE and hold, continue climb-in-hold to 3100.

CQF AWOS-3PT
118.425

PENSACOLA APP CON
118.6 380.6

UNICOM
123.05 (CTAF) 0



ELEV 74

TDZE 73

3100

RUPQE

AWAGE

WIBIK

HEKAL

2.5 NM to RW36

3700 X 74

81

0.3% UP

36

3000

4 NM Holding Pattern

1500

900

3.00° TCH 38

2.5 NM

1.9 NM

6.1 NM

MIRL Rwy 18-36 0

002°

CATEGORY	A	B	C	D
LP MDA	500-1	427 (500-1)	500-1¼ 427 (500-1¼)	NA
LNAV MDA	500-1	427 (500-1)	500-1¼ 427 (500-1¼)	NA
CIRCLING	680-1	606 (700-1)	880-2¼ 806 (900-2¼)	NA