


KINGDOM FIVE DEPARTURE

LONE STAR DEP CON
118.1 306.95
ATTIS
126.925
CINC DEL
128.725
GND CON
132.65 306.2
ALLIANCE TOWER
135.15 257.9

TOP ALTITUDE:
ASSIGNED BY ATC

TAKEOFF MINIMUMS
Rwys 34L/R: Standard.
Rwys 16L: 300-2 ¼ or standard with minimum climb of 220'/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1900' prior to DER.
Rwys 16R: 300-2 ¼ or standard with minimum climb of 225'/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 2000' prior to DER.

RADAR and DME required.



NOTE: LUBBOCK Transition: For all aircraft overlying the MQP VORTAC westbound or direct.
NOTE: MILLSAP Transition: For all aircraft overlying the MQP VORTAC westbound or direct.
NOTE: PODDE Transition: ATC assigned.
NOTE: WICHITA FALLS Transition: For all aircraft landing within the Wichita Falls terminal area or overlying the SPS VORTAC.
NOTE: For all aircraft requesting 17000 and below.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

KINGDOM FIVE DEPARTURE