

APP CRS
185°

Rwy Ldg
TDZE
Apt Elev

3499
247
247

RNAV (GPS) RWY 18

CHARLES W BAKER (2M8)


RNP APCH - GPS.

▼
NA

Rwy 18 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Millington/Memphis altimeter setting and increase all MDA 40 feet; and LNAV Cat C visibility ⅛ SM and Circling Cat C visibility ¼ SM. Straight-in Rwy 18 NA at night, Circling Rwy 18 NA at night.

MISSED APPROACH: Climb to 1200 then climbing left turn to 3000 direct HACHE and hold.

AWOS-3PT 119.575	MEMPHIS APP CON 125.8 338.3	UNICOM 122.8 (CTAF)
---------------------	--------------------------------	------------------------



ELEV 247

TDZE 247

185°

81

3499 X 75

36

1600 X 75

36U

MIRL Rwy 18-36
REIL Rws 18 and 36

1200

3000

HACHE

VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 40).

RW18

DIPJO

EVACO

820

1800

3000

1.4 NM

2.5 NM

6.1 NM

CATEGORY	A	B	C	D
LNAV MDA	780-1	533 (600-1)	780-1½ 533 (600-1½)	NA
CIRCLING	780-1 533 (600-1)	860-1 613 (700-1)	900-1¾ 653 (700-1¾)	NA