25 DEC 2025 to 22 JAN 2026

WEAZL FIVE DEPARTURE (RNAV) CONCORD. NORTH CAROLINA RNAV 1 - DME/DME/IRU or GPS. **TOP ALTITUDE:** CHARLOTTE DEP CON 128.325 307.8 3000 RADAR required. ATIS 133.675 CINC DEL 118.55 CLNC DEL (when twr closed) CLAWD ≺ **GND CON** 121.85 CONCORD TOWER ★ 134.65 UNICOM 122.95 **TAKEOFF MINIMUMS** Rwy 2: Standard. Rwy 20: Standard with minimum climb of 320' per NM to 2400. 14300 6400 003 (45) NOTE: For turbo jets only. If unable to accept climb rates, NOTE: advise ATC on initial contact. NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC. WEAZL ≺



NSA JQF 25 M 3800

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb on heading 016° to 2200, then on heading assigned by ATC,

TAKEOFF RUNWAY 20: Climbing left turn heading 150° to 2400, then on heading assigned by ATC, thence. . . .

. . . . on RADAR vectors to WHFRD, then on track 003° to WEAZL, then on CLAWD Transition. Maintain 3000, expect clearance to filed altitude within 10 minutes after departure.

CLAWD TRANSITION (WEAZL5.CLAWD)

WHFRD

NOTE: Chart not to scale.

2400