

APP CRS
031°

Rwy Idg
TDZE
Apt Elev

4000
648
658

RNAV (GPS) RWY 3

RUBY (RBY) (PARY)

When local altimeter setting not received, use Galena altimeter setting and increase all MDA 340 feet and all visibilities ¾ SM. DME/DME RNP-0.3 NA.
Rwy 3 Straight-in and Circling minimums NA at night. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:
Climbing right turn to 3800 direct WINUR and hold.

AWOS-3P 118.25	ANCHORAGE CENTER 127.0 290.2	FAIRBANKS RADIO 122.25	CTAF 122.8
-------------------	---------------------------------	---------------------------	---------------

The main chart displays the RNAV route for RWY 3. Key waypoints and data include:
- WINUR: 3800 ft, 30 NM to WINUR (NoPT) at 120° and 301°.
- 5 NM Holding Pattern for WINUR: 3800 ft, 210° and 030°.
- TINUC: 2700 ft, 030° and 210°.
- YARUN: 2700 ft, 031° and 1800 ft.
- DUCCEL: 3800 ft, 30 NM to DUCCEL at 100° and 301°.
- ZUMUN: 3800 ft, 10 NM to ZUMUN at 120° and 211°.
- SOLCO: 665 ft, 2.9 NM to SOLCO.
- GALENA MOA: 1780 ft.
- ELEV 658, TDZE 648.

Visual Segment - Obstacles.

3800 WINUR

5 NM Holding Pattern

3800 ← 210°
→ 030°

030°

2700

031°

1800

6.2 NM

3.2 NM

2.9 NM

0.1

YARUN 2.9 NM to SOLCO

SOLCO

0.25% UP

4000 X 100

031°

CATEGORY	A	B	C	D
LNVA MDA	1260-1	612 (700-1)	1260-1¾ 612 (700-1¾)	NA
CIRCLING	1260-1 602 (700-1)	1400-1 742 (800-1)	1400-2¼ 742 (800-2¼)	NA

REIL Rwy 21
MIRL Rwy 3-21

RUBY, ALASKA

Amtd 1C 02DEC21

64°44'N-155°28'W

RUBY (RBY) (PARY)

RNAV (GPS) RWY 3