YODUH TWO DEPARTURE (RNAV) SAN ANTONIO, TEXAS SAN ANTONIO DEP CON RNAV 1 - DME/DME IRU or GPS. TOP ALTITUDE: 125.1 307.0 RADAR required for non-GPS equipped aircraft. **ASSIGNED BY ATC** RADAR required. NOTE: Aircraft destined for airports north/northeast of DFW terminal area must file the KLNGR Transition. PRTZY **KLNGR** TAKEOFF MINIMUMS Rwy 17: Standard with minimum climb of 210'/NM to 2200. Rwy 35: Standard with minimum climb of 250'/NM to 3800. SITHH 5000



22 JAN 2026

2

25 DEC 2025

SC-3,

NOTE: Chart not to scale.

V

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 17: Climb on heading 169° or as assigned by ATC, for vectors to SITHH, thence. . . TAKEOFF RUNWAY 35: Climb on heading 349° or as assigned by ATC, for vectors to SITHH, thence. . .

. . . on track 002° to YODUH, then on transition. Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure.

KLNGR TRANSITION (YODUH2.KLNGR) PRTZY TRANSITION (YODUH2.PRTZY)