

WAAS CH 72817 W13A	APP CRS 133°	Rwy Ldg 5720 TDZE 67 Apt Elev 70
--	------------------------	---

RNAV (GPS) RWY 13

BATON ROUGE METRO, RYAN FLD (BTR)

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -55°C (23°F) or above 54°C (130°F). DME/DME RNP 0.3 NA. When local altimeter setting not received, use Hammond altimeter setting and increase all DA 91 feet and all MDA 100 feet, and increase LNAV/VNAV all Cats visibility ¼ mile, and LNAV Cats C and D visibility ½ mile. For inop MALSR when using Hammond altimeter setting, increase LPV all Cats visibility to ½ mile, LNAV Cat C and D visibility to 1 ½ mile. Baro-VNAV and VDP NA when using Hammond altimeter setting.

MALS



MISSED APPROACH: Climb to 2300 direct FADAD and hold.

ATIS 125.2	BATON ROUGE APP CON ★ 120.3 278.3	RYAN TOWER ★ 118.45 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 119.4	UNICOM 122.95
----------------------	---	--	-------------------------	--------------------------	-------------------------

