

WAAS CH 72800 W 17B	APP CRS 172°	Rwy Ldg TDZE 6177 Apt Elev 6187
---	------------------------	---

RNAV (GPS) Y RWY 17R



CITY OF COLORADO SPRINGS MUNI (COS)

RNP APCH - GPS.

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C.
 ⚠ Simultaneous approach authorized with ILS or LOC RWY 17L and ILS RWY 17L (SA CAT I).
 LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MISSED APPROACH: Climb to 7000 then climbing left turn to 9000 direct DRAKE and hold.

ATIS 125.0 254.3	SPRINGS APP CON 124.0 257.875	SPRINGS TOWER 119.9 360.6	GND CON 121.7 348.6	CLNC DEL 134.45 363.125
----------------------------	---	-------------------------------------	-------------------------------	-----------------------------------



ELEV	6187	TDZE	6177
LPV	DA	6377/40 200 (200-¾)	
LNAV/VNAV	DA	6752-2 575 (600-2)	
LNAV	MDA	6680/55 503 (500-1)	6680-1⅜ 503 (500-1⅜)
CIRCLING		6740-1 553 (600-1) 613 (700-1)	7040-2½ 853 (900-2½) 7260-3 1073 (1100-3)

MIRL Rwy 13-31
 TDZ/CL Rwy 17L and 35R
 REIL Rwy 13, 17R, 31 and 35R
 HIRL Rwy 17R-35L and 17L-35R

SW-1, 22 JAN 2026 to 19 FEB 2026

SW-1, 22 JAN 2026 to 19 FEB 2026