


WAAS CH 69424 W23A	APP CRS 231°	Rwy Ldg TDZE 16 Apt Elev 17
--	------------------------	---

RNAV (GPS) RWY 23
PAGE FLD (FMY)

RNP APCH - GPS.	MISSED APPROACH: Climb to 2000 direct CALOO LOM and hold, continue climb-in-hold.
▼ ▲ Rwy 23 helicopter visibility reduction below ¾ SM NA. When Circling to Rwy 31 at night, operational VGSI required, remain on or above VGSI glidepath until threshold. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 5°C or above 54°C.	

ATIS 123.725	FORT MYERS APP CON ★ 125.15 306.2 (Rwys 5, 13) 126.8 306.2 (Rwys 23, 31)	PAGE TOWER ★ 119.0 (CTAF) 0 306.95	GND CON 121.7	CLNC DEL 121.7
------------------------	--	---	-------------------------	--------------------------



ELEV 17		D		TDZE 16	
2000		CALOO			
RW23		EBAXE 2 NM to RW23		GLUMM 1600	
1.1 NM to RW23		2.8 NM		6.1 NM	
A		B		C	
D					
CATEGORY					
LPV DA	278-7/8 262 (300-7/8)				
LNAV/VNAV DA	392-1 376 (400-1)				
LNAV MDA	440-1 424 (500-1)		440-1¼ 424 (500-1¼)		
CIRCLING	540-1 523 (600-1)		600-1½ 583 (600-1½)		680-2 663 (700-2)

SE-3, 22 JAN 2026 to 19 FEB 2026

SE-3, 22 JAN 2026 to 19 FEB 2026