



LOC/DME I-PDK 111.1 Chan 48	APP CRS 206°	Rwy Ldg TDZE 991 Apt Elev 998
--	------------------------	---

ILS or LOC RWY 21L
DEKALB-PEACHTREE (PDK)

RADAR required for procedure entry. DME or RADAR required.		MALSF 	MISSED APPROACH: Climb to 1600 then climbing right turn to 4000 on heading 008° and on RMG VORTAC R-092 to BAPPY/RMG 34.7 DME/RADAR and hold.
	Circling Rwy 16, 34 NA at night. Rwy 21L helicopter visibility reduction below RVR 4000 NA.		

ATIS 128.4	ATLANTA APP CON 126.975 239.275	PEACHTREE TOWER ★ 120.9 (CTAF) 281.5	GND CON 121.6	UNICOM 122.95	120.0
----------------------	---	--	-------------------------	-------------------------	--------------



1600	4000	RMG R-092	BAPPY	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 55).	One Minute Holding Pattern	
		hdg 008°			AABEE I-PDK 12.9 RADAR	
Glide slope unusable for coupled approach below 1900.				CHAMB I-PDK 6.8 RADAR	5400	3000
				I-PDK 0.9	2900	2900
				I-PDK 2.4	2900	2900
				1.5 NM	4.3 NM	6.1 NM
CATEGORY	A	B	C	D		
S-ILS 21L	1330/40		339 (400-3/4)			
S-LOC 21L	1520/40		529 (600-3/4)		1520-1 1/4 529 (600-1 1/4)	
CIRCLING	1520-1		522 (600-1)		1840-2 1/2 842 (900-2 1/2) 2060-3 1062 (1100-3)	