


APP CRS	Rwy Ldg	7110
211°	TDZE	404
	Apt Elev	410

RNAV (RNP) Z RWY 21R

TRI-CITIES (PSC)


For uncompensated Baro-VNAV systems, procedure NA below -14°C (7°F) or above 54°C (130°F). GPS required. RF required. For inoperative MALSR, increase RNP 0.11 all Cnts visibility to RVR 5700 and RNP 0.30 all Cnts visibility to 1½ mile.	MALSR	MISSED APPROACH: Climb to 5200 on track 211° to KARTE, right turn to DAMSE, and on track 332° to PAIDS and hold.
--	--------------	---

ATIS 125.65	SPOKANE APP CON * 128.75 377.2	TRI-CITIES TOWER * 135.3 (CTAF) 0 285.55	GND CON 121.8	UNICOM 122.95
----------------	-----------------------------------	---	------------------	------------------




ELEV 410	TDZE 404
----------	----------

5200	KARTE	DAMSE	tr 332°	PAIDS
tr 211°				



CATEGORY	A	B	C	D
RNP 0.11 DA		754/33	350 (400-½)	
RNP 0.30 DA		832/48	428 (500-1)	

AUTHORIZATION REQUIRED



NW-1, 22 JAN 2026 to 19 FEB 2026

NW-1, 22 JAN 2026 to 19 FEB 2026