

WAAS CH 57907 W21A	APP CRS 214°	Rwy Ldg TDZE Apt Elev	6500 522 547
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 21

BOWLING GREEN-WARREN COUNTY RGNL (BWG)

RNP APCH - GPS.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C. Baro-VNAV and VDP NA when using GLW altimeter setting. Circling Rwy 30 NA at night. Rwy 21 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use GLW altimeter setting and increase LPV DA to 884 feet and all visibilities ⅓ SM. Increase LNAV/VNAV DA to 1150 feet and all visibilities ⅓ SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM.

MISSED APPROACH: Climb to 3100 direct WEDVO and hold.

ASOS
127.825

MEMPHIS CENTER
133.85 285.5

UNICOM
123.0 (CTAF) 0

Diagram illustrating the RNAV (GPS) RWY 21 approach procedure, showing various waypoints, altitudes, and distances. Key features include: JIBIP (IAF), UGATE (IF/IAF), ZEZTA (FAF), XOMYU, WISLI, and RW21. Altitudes range from 660 to 6500 feet. Distances are marked in NM. A missed approach fix is shown near WEDVO. A diagram of the runway layout is included at the bottom left.

ELEV 547

D

TDZE 522

Diagram illustrating the runway layout, showing Runway 21 (1200x3000 ft) and Runway 3 (3000x150 ft). It also shows the location of Runway 12-30 and Runway 3-21.

REIL Rwy 3 and 21

MIRL Rwy 12-30

HIRL Rwy 3-21

3100	WEDVO	WISLI 2.1 NM to RW21	ZEZTA 2400	UGATE 4 NM Holding Pattern																									
1.4 NM	0.7 NM	3.6 NM	6 NM																										
<table><tr><td>CATEGORY</td><td>A</td><td>B</td><td>C</td><td>D</td></tr><tr><td>LPV DA</td><td colspan="4">807-7/8 285 (300-7/8)</td></tr><tr><td>LNAV/VNAV DA</td><td colspan="4">1073-15/8 551 (600-15/8)</td></tr><tr><td>LNAV MDA</td><td>1020-1 498 (500-1)</td><td colspan="3">1020-13/8 498 (500-13/8)</td></tr><tr><td>CIRCLING</td><td>1020-1 473 (500-1)</td><td>1120-1 573 (600-1)</td><td>1160-13/4 613 (700-13/4)</td><td>1200-2 653 (700-2)</td></tr></table>					CATEGORY	A	B	C	D	LPV DA	807-7/8 285 (300-7/8)				LNAV/VNAV DA	1073-15/8 551 (600-15/8)				LNAV MDA	1020-1 498 (500-1)	1020-13/8 498 (500-13/8)			CIRCLING	1020-1 473 (500-1)	1120-1 573 (600-1)	1160-13/4 613 (700-13/4)	1200-2 653 (700-2)
CATEGORY	A	B	C	D																									
LPV DA	807-7/8 285 (300-7/8)																												
LNAV/VNAV DA	1073-15/8 551 (600-15/8)																												
LNAV MDA	1020-1 498 (500-1)	1020-13/8 498 (500-13/8)																											
CIRCLING	1020-1 473 (500-1)	1120-1 573 (600-1)	1160-13/4 613 (700-13/4)	1200-2 653 (700-2)																									

BOWLING GREEN, KENTUCKY

Amdt 1B 12JUN25

BOWLING GREEN-WARREN COUNTY RGNL (BWG)

36°58'N-86°25'W

RNAV (GPS) RWY 21