



APP CRS	Rwy Ldg	9400
178°	TDZE	35
	Apt Elev	36

RNAV (RNP) Z RWY 18R
VALLEY INTL (HRL)

RNP AR APCH - GPS.		MALSR 	MISSED APPROACH: Climb to 500 then climbing left turn to 2000 direct RELAX and hold.	
 For uncompensated Baro-VNAV systems, procedure NA below -1°C or above 54°C. When local altimeter setting not received, procedure NA. For inop ALS, increase RNP 0.11 all Cats visibility to RVR 4000 and RNP 0.30 all Cats visibility to RVR 4500.				
ATIS 124.85	VALLEY APP CON 120.7 279.5	HARLINGEN TOWER★ 119.3(CTAF) 0 317.6	GND CON 121.7	UNICOM 122.95



ELEV 36	D	TDZE 35
---------	----------	---------



NSCAR
4000 210K

MISSED APCH FIX

4 NM

RELAX

3.55°

17.5°

500 2000 RELAX

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 71)

CIXEN

1400

178°

1400

GP 3.00°
TCH 55

See planview for multiple IF locations.

4.1 NM

CATEGORY	A	B	C	D
RNP 0.11 DA		285/24	250 (300-½)	
RNP 0.30 DA		345/24	310 (400-½)	

AUTHORIZATION REQUIRED

RNAV (RNP) Z RWY 18R