

WAAS CH 99704 W35A	APP CRS 347°	Rwy Ldg TDZE Apt Elev	5000 1864 1864
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35


RUSSELL MUNI (RSL)

⚠

Baro-VNAV NA when using Hays altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.
VDP NA when using Hays altimeter setting. When local altimeter setting not received, use Hays altimeter setting: increase LPV all Cats DA to 2187 feet, LNAV/VNAV all Cats DA to 2267 feet and all visibilities ¼ SM; increase all MDA 80 feet, LNAV Cat C visibility ⅓ SM and Circling Cat C visibility ¼ SM. Circling NA to Rwys 3 and 21.

MISSED APPROACH:
Climb to 4000 direct
EDITE and hold.

ASOS 128.325	KANSAS CITY CENTER 124.4 322.4	UNICOM 122.7 (CTAF) 0
------------------------	--	---------------------------------



4000		EDITE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 42).		5 NM
*LNAV only.		*0.9 NM to RW35		AMUKE	BAQFO Holding Pattern
RW35		0.9 NM		347°	4000
3500		4.1 NM		347°	GP 3.00° TCH 35
6.5 NM					
CATEGORY	A	B	C	D	
LPV DA	2118-1	254 (300-1)		NA	
LNAV/VNAV DA	2198-1½	334 (400-1½)		NA	
LNAV MDA	2200-1	336 (400-1)		NA	
CIRCLING	2240-1 376 (400-1)	2320-1 456 (500-1)	2620-2¼ 756 (800-2¼)	NA	