ZAAPA SIX DEPARTURE (RNAV)

(ZAAPA6.ZAAPA) 27NOV25

CLEVELAND, OHIO
CUYAHOGA COUNTY (CGF)

CLEVELAND DEP CON
125.35 346.325
D-ATIS
119.95
CLNC DEL
121.85 (when twr closed)
GND CON
121.85
COUNTY TOWER ★
118.5 (CTAF)

RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

TOP ALTITUDE: ASSIGNED BY ATC

TAKEOFF MINIMUMS:
Rwys 6, 24: Standard with minimum climb of 500′ per NM to 1400.

NOTE: PUUDL TRANSITION: For aircraft at or below FL220 only or as assigned by ATC.





NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 6: Climb on heading 057° to 1900, then on heading 330° or as assigned by ATC for RADAR vectors to cross MOHUM at or above 9000, thence....
TAKEOFF RUNWAY 24: Climb on heading 237° to 1900, then right turn heading 330° or as assigned by ATC for RADAR vectors to cross MOHUM at or above 9000, thence....

....on track 259° to cross ZAAPA at or below 14000, then on (transition). Maintain ATC assigned altitude, expect filed altitude ten minutes after departure.

PUUDL TRANSITION (ZAAPA6.PUUDL)
SINKR TRANSITION (ZAAPA6.SINKR)
SNNOH TRANSITION (ZAAPA6.SNNOH)

(ZAAPA6.ZAAPA) 25331
ZAAPA SIX DEPARTURE (RNAV)
AL-5027 (FAA)
CUYAHOGA COUNTY (CGF)
CLEVELAND, OHIO