

ILS or LOC RWY 1C  
WASHINGTON DULLES INTL (IAD)

DME or RADAR required.  
RADAR required for procedure entry at BRODY.

**T** Simultaneous approach authorized. DME from AML VOR/DME.  
**A** DME use requires simultaneous reception of I-OSZ and AML DME.  
 For inop ALS, increase S-LOC Cats C/D visibility to RVR 5500.

**MISSED APPROACH:** Climb to 4000 on AML VOR/DME R-010 to CHDMN/AML 16.9 DME/RADAR and hold, continue climb-in-hold to 4000.

**ARML 113.5 AML Chan 82**

**LOCALIZER 111.3 I-OSZ**

**MSA AML 25 NM**

**ELEV 312 TDZE 286**

**TDZL/RCLS Rwy 1C, 1L, 1R, 12, 19C and 19R**

**REIL Rwy 30**

**HIRL all rwy**

| CATEGORY | A                  | B           | C                      | D                       |
|----------|--------------------|-------------|------------------------|-------------------------|
| S-ILS 1C | 486/18 200 (200-½) |             |                        |                         |
| S-LOC 1C | 640/24             | 354 (400-½) | 640/30                 | 354 (400-¾)             |
| CIRCLING | 940-1              | 628 (700-1) | 940-1¾<br>628 (700-1¾) | 1180-2¾<br>868 (900-2¾) |