

APP CRS
179°

Rwy Ldg
TDZE
Apt Elev

4855
912
912

RNAV (GPS) RWY 18


ANOKA COUNTY/BLAINE (JANES FLD) (A.N.E.)

RNP APCH - GPS.

When local altimeter setting not received, use Crystal altimeter setting and increase all MDA 40 feet and Circling Cat D visibility ¼ SM.
VDP NA when using Crystal altimeter setting.

MISSED APPROACH: Climbing left turn to 2600 direct RUNRR and hold.

ATIS 120.625	MINNEAPOLIS APP CON 126.5 335.65	ANOKA TOWER★ 132.4 (CTAF) 0	GND CON 121.85	UNICOM 122.95
------------------------	--	---------------------------------------	--------------------------	-------------------------



ELEV 912

TDZE 912

179°

81

4855 X 100

5000 X 100

6

TWR

36

☆

HIRL Rwy 9-27 0

MIRL Rwy 18-36 0

REIL Rws 9, 18 and 36 0

2600

RUNRR

DOZXU

RUNRR

4 NM Holding Pattern

1.3 NM to RWY 18

3.00° TCH 50

179°

359°

2600

2100

1.3 NM

2.3 NM

6.1 NM

CATEGORY	A	B	C	D
RNAV MDA	1380-1	468 (500-1)	1380-1 3/8	468 (500-1 3/8)
CIRCLING	1400-1	488 (500-1)	1460-1 1/2	1580-2
			548 (600-1 1/2)	668 (700-2)