

LOC I-IWD
111.5

APP CRS
270°

Rwy Ldg
TDZE
Apt Elev
6501
1230
1230

ILS or LOC RWY 27

GOGEBIC/IRON COUNTY (IWD)

▼

▲ NA

☄ -26°C

When local altimeter setting not received, use ASX altimeter setting: increase DA to 1562 feet; increase all MDAs 140 feet and S-LOC 27 visibility Cats C and D ½ SM and Circling visibility Cat B ¼ SM. For inop ALS when using ASX altimeter setting, increase S-ILS 27 all Cats visibility to 1 SM.

MALSR

MISSED APPROACH:
Climb to 3300 then
right turn direct IWD
VOR/DME and hold.

AWOS-3PT 125.175	MINNEAPOLIS CENTER 133.55	UNICOM 122.8 (CTAF) 1
----------------------------	-------------------------------------	---------------------------------

Diagram illustrating the approach procedure for ILS or LOC RWY 27. Key features include:

- IAF IRONWOOD 108.8 IWD Chan 25
- LOC 111.5 I-IWD
- Altitudes: 1840±, 1419±, 1274, 1869±, 2093, 2124±, 2093
- Angles: 259°, 079°, 270°, 045°, 225°, 090°
- MSA IWD 25 NM (3200)
- KLAAV OM IWD 3.5
- R-259

Diagram illustrating the approach procedure for ILS or LOC RWY 27, showing the final approach segment and altitude restrictions:

- 3300
- IWD VOR/DME
- 090°
- KLAAV OM IWD 3.5
- 2311
- 270°
- 3300
- 2800
- 2500* (LOC only)
- GS 3.00°
- TCH 55
- 3.2 NM
- Remain within 15 NM of IWD VOR/DME

CATEGORY	A	B	C	D
S-ILS 27		1430-½	200 (200-½)	
S-LOC 27	1720-½	490 (500-½)	1720-1	490 (500-1)
CIRCLING	2100-1¼	870 (900-1¼)	2200-3 970 (1000-3)	2220-3 990 (1000-3)

ELEV 1230 D TDZE 1230

Diagram illustrating the final approach segment and altitude restrictions:

- 6502 X 100
- 1307
- 270°
- REIL Rwy 9 1
- HIRL Rwy 9-27 1
- FAF to MAP 3.2 NM

Knots	60	90	120	150	180
Min:Sec	3:12	2:08	1:36	1:17	1:04

IRONWOOD, MICHIGAN

Amdt 3D 26DEC24

46°32'N-90°08'W

GOGEBIC/IRON COUNTY (IWD)

ILS or LOC RWY 27

EC-1, 22 JAN 2026 to 19 FEB 2026

EC-1, 22 JAN 2026 to 19 FEB 2026