

WAAS CH 65920 W13A	APP CRS 128°	Rwy Ldg 5639 TDZE 1182 Apt Elev 1183
--	------------------------	---

RNAV (GPS) RWY 13


FERGUS FALLS RGNL (FFM)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.
When local altimeter setting not received, use Elbow Lake altimeter setting and increase LPV DA to 1428 feet, increase LNAV/VNAV DA to 1516 feet and all visibilities ½ SM;
increase all MDAs 60 feet and LNAV Cat C/D and Circling Cat C/D visibility ½ SM.
Baro-VNAV and VDP NA when using Elbow Lake altimeter setting.

MISSED APPROACH:
Climb to 2900 direct
IGAKE and hold.

AWOS-3PT 119.05	MINNEAPOLIS CENTER 126.1 269.2	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 52).				
4 NM Holding Pattern CUKVU				
GP 3.00° TCH 40				
6000 2900 308° 128° 2900 1760 1.1 NM to RW13 0.6 1.1 NM				
6.1 NM 3.6 NM				
CATEGORY	A	B	C	D
LPV DA	1382-¾ 200 (200-¾)			
LNAV/VNAV DA	1470-7/8 288 (300-7/8)			
LNAV MDA	1580-1	398 (400-1)	1580-1½	398 (400-1½)
CIRCLING	1640-1 457 (500-1)	1740-1 557 (600-1)	1820-1¾ 637 (700-1¾)	1940-2½ 757 (800-2½)

REIL Rwy 13 and 35 0
MIRL Rwy 13-31 and 17-35 0