

APP CRS	Rwy Idg	3301
060°	TDZE	1215
	Apt Elev	1215


RNAV (GPS) RWY 6
MARSHALL COUNTY (MPG)

RNP APCH.

▼ Rwy 6 helicopter visibility reduction below ¾ SM NA. VDP NA when using Wheeling altimeter setting. When local altimeter setting not received, use Wheeling altimeter setting: increase all MDA 60 feet and visibility LNAV Cat C ½ SM and Circling Cat C ¼ SM.

▲ NA MISSED APPROACH: Climb to 3100 direct EWBUF and hold.

AWOS-3 119.05	CLEVELAND CENTER 126.95 239.30	UNICOM 122.7 (CTAF) ①
------------------	-----------------------------------	--------------------------



ELEV 1215 TDZE 1215				
4 NM Holding Pattern MEHIF Visual Segment - Obstacles. 3100 EWBUF JUMSU 1.5 NM to RW06 RW06 3000 ← 240° 060° → 060° 2800 6.3 NM 3.3 NM 1.5 NM				
CATEGORY	A	B	C	D
LNAV MDA	1860-1	645 (700-1)	1860-1⅞ 645 (700-1⅞)	NA
CIRCLING	1860-1	645 (700-1)	1940-2 725 (800-2)	NA

3301 X 60

0.8% UP

060°

MIRL Rwy 6-24

NE-4, 22 JAN 2026 to 19 FEB 2026

NE-4, 22 JAN 2026 to 19 FEB 2026