



WAAS CH 60901 W09B	APP CRS 094°	Rwy Ldg 10181 TDZE 32 Apt Elev 33
--	------------------------	--


RNAV (GPS) RWY 9R
MELBOURNE ORLANDO INTL (MLB)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 2000 direct ZUVOM and hold.
	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C.		

ATIS 132.55	ORLANDO APP CON 126.025 281.425	MELBOURNE TOWER ★ 118.2 (CTAF) 257.8	GND CON 121.9	UNICOM 122.95
-----------------------	---	---	-------------------------	-------------------------



CATEGORY	A	B	C	D
LPV DA	232/18		200 (200-½)	
LNAV/VNAV DA	427/35		395 (400-⅝)	
LNAV MDA	480/24	448 (500-½)	480/45	448 (500-⅞)
CIRCLING	500-1 467 (500-1)	560-1 527 (600-1)	680-1¾ 647 (700-1¾)	880-2¾ 847 (900-2¾)



SE-3, 19 FEB 2026 to 19 MAR 2026

SE-3, 19 FEB 2026 to 19 MAR 2026