TOP ALTITUDE: FL230

RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

TAKEOFF MINIMUMS
Rwys 14, 32: NA-ATC.
Rwy 16L: Standard with minimum climb of 470′ per NM to 9900.
Rwy 16R: Standard with minimum climb of 500′ per NM to 9700.
Rwy 17: Standard with minimum climb of 425′ per NM to 9400.
Rwy 34L: Standard with minimum climb of 250′ per NM to 8500.
Rwy 34R: Standard with minimum climb of 310′ per NM to 11500.
Rwy 35: Standard with minimum climb of 305′ per NM to 11500.

NOTE: Turbojet aircraft only.
NOTE: Aircraft landing Denver Intl Airport, file the PERTY Transition.

D-ATIS
124.75 125.625
CLNC DEL
127.3 379.975
CPDLC
GND CON
121.9 348.6 (Rwys 14-32, 17-35)
123.775 348.6 (Rwys 16L-34R, 16R-34L)
SALT LAKE CITY TOWER
119.05 257.8 (Rwy 16L-34R)
118.3 257.8 (Rwys 14-32, 17-35)
132.65 336.4 (Rwy 16R-34L)
SALT LAKE CITY DEP CON
135.5 316.15