

APP CRS
334°

Rwy Idg
TDZE
Apt Elev

4000
928
928

RNAV (GPS) RWY 33

KNOXVILLE MUNI (OXV)

▼

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.

▲

Baro-VNAV and VDP NA when using Pella altimeter setting.

When local altimeter setting not received, use Pella altimeter setting and increase all DA 29 feet, all MDA 40 feet, LNAV/VNAV all Cats visibility ¼ mile.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F).

MISSED APPROACH: Climb to 3000 direct JOEBB and hold.

AWOS-3 119.775	DES MOINES APP CON 123.9 307.15	UNICOM 122.8 (CTAF) 0
-------------------	------------------------------------	--------------------------

MISSED APCH FIX

Procedure NA for arrivals at BUSSY via V52 southeast bound.

Procedure NA for arrivals at LACON via V175 northwest bound.

ELEV 928

TDZE 928

MIRL Rwy 15-33 0

REIL Rwy 15 and 33 0

3000	JOEBB	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 32).	4 NM Holding Pattern	
*LNAV only.	*1.4 NM to RW33	LEGWU	2700	
	FIXAB	334°	154°	
1.4 NM	3.4 NM	6.3 NM	GP 3.00° TCH 40	
CATEGORY	A	B	C	D
LNAV/VNAV DA	1299-1¼	371 (400-1¼)	NA	NA
LNAV MDA	1400-1	472 (500-1)	NA	NA
CIRCLING	1480-1	552 (600-1)	NA	NA

KNOXVILLE, IOWA

Orig 08APR10

41°18'N-93°07'W

KNOXVILLE MUNI (OXV)

RNAV (GPS) RWY 33