

RADAR INSTRUMENT APPROACH MINIMUMS

LEMOORE NAS (REEVES FIELD) (KNLC)

Lemoore, CA Amdt 9 12JUN25 (25163) (USN)

ELEV 228

RADAR - (E) 125.95 270.8x 314.0x 317.575x 322.45x 323.15x 336.4x 346.375x 348.75x 353.55x
363.7x 370.875x 377.075x **T**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA/ HATh/</u>	<u>CEIL-VIS</u>
PAR ^{1,2}	32L ^{3,4}	3.0°/40/762	ABCDE	327 - ¹ / ₄	100	(100- ¹ / ₄)
	14L	3.0°/54/1019	ABCDE	319 - ¹ / ₂	100	(100- ¹ / ₂)
	14R ⁵	3.0°/52/998	ABCDE	328 - ¹ / ₂	100	(100- ¹ / ₂)
	32R ⁵	3.0°/46/876	ABCDE	321 - ¹ / ₂	100	(100- ¹ / ₂)
ASR ²	32L ^{6,7}		AB	600 - ¹ / ₂	373	(400- ¹ / ₂)
			CDE	600 - ⁵ / ₈	373	(400- ⁵ / ₈)
	14L		AB	680 -1	461	(500-1)
			CDE	680 -1 ³ / ₈	461	(500-1 ³ / ₈)
	14R ⁵		AB	760 -1	532	(600-1)
			CDE	760 -1 ¹ / ₂	532	(600-1 ¹ / ₂)
32R ⁵		AB	780 -1	559	(600-1)	
		CDE	780 -1 ⁵ / ₈	559	(600-1 ⁵ / ₈)	
CIR ⁸	14L, 32L		AB	680 -1	452	(500-1)
			C	680 -1 ¹ / ₂	452	(500-1 ¹ / ₂)
			D	780 -2	552	(600-2)
			E	800 -2	572	(600-2)
	14R		AB	760 -1	532	(600-1)
			C	760 -1 ¹ / ₂	532	(600-1 ¹ / ₂)
			D	780 -2	552	(600-2)
			E	800 -2	572	(600-2)
	32R		AB	780 -1	552	(600-1)
			C	780 -1 ⁵ / ₈	552	(600-1 ⁵ / ₈)
			D	780 -2	552	(600-2)
			E	800 -2	572	(600-2)

19 FEB 2026 to 19 MAR 2026

19 FEB 2026 to 19 MAR 2026

¹No-NOTAM MP: PAR-Rwy 14R-32L 1600-2400Z++ Mon, Rwy 14L-32R 1600-2400Z++ Wed.

²Simultaneous approaches authorized.

³When ALS inop, increase vis to ¹/₂ mile.

⁴Caution: WCH 15 ft for group 4 less than required 20 ft.

⁵Pattern at 3000 ft.

⁶When ALS inop, increase vis to 1 mile.

⁷Step Down Fix at 3 NM from thld, 1100 min.

⁸Circling authorized only from ASR.

RADAR INSTRUMENT APPROACH MINIMUMS