RNAV (GPS) RWY 17L
SOUTH TEXAS RGNL AT HONDO (HDO)

WAAS CH 69619 W17A	APP CRS 172°	Rwy ldg 6002 TDZE 929 Apt Elev 930

RNP APCH.

Baro-VNAV and VDP NA when using Castroville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. When local altimeter setting not received, use Castroville altimeter setting and increase all DA 62 feet and all MDA 80 feet, increase LNAV/VNAV all Cats visibility ⅛ SM, LNAV and Circling Cats C/D visibility ¼ SM. Rwy 17L helicopter visibility reduction below ¾ SM NA. Circling to Rwys 8, 13, 17R, 26, 31 and 35L NA at night.

MISSED APPROACH: Climb to 4000 direct MUNJO and hold, continue climb-in-hold to 4000.

ASOS	HOUSTON CENTER	UNICOM
119.675	134.95 269.4	122.725 (CTAF)





CATEGORY	A	B	C	D
LPV DA	1179-1 250 (300-1)			
LNAV/VNAV DA	1314-1¼ 385 (400-1¼)			
LNAV MDA	1420-1 491 (500-1)		1420-1⅜ 491 (500-1⅜)	1420-1½ 491 (500-1½)
CIRCLING	1440-1 510 (600-1)	1520-1 590 (600-1)	1580-1¾ 650 (700-1¾)	1580-2 650 (700-2)