

LUFKIN FOUR DEPARTURE

HOUSTON DEP CON
134.45 284.0
ATIS
135.575 269.9
GND CON
121.6 275.8
ELLINGTON TOWER
126.05 253.5

**TOP ALTITUDE:
ASSIGNED BY ATC**

LITTLE ROCK
115.1 LIT :::::
Chan 98

RADAR and DME required.

NOTE: For aircraft destined LIT or overflying LIT or PXV.

TAKEOFF MINIMUMS

Rwys 4, 17L/R, 35L/R: Standard.
Rwy 22: 300-1¼ or standard with minimum
climb of 220'/NM to 300 or
alternatively with standard takeoff
minimums and a normal 200'/NM
climb gradient, takeoff must occur
no later than 1500' prior to DER.

LUFKIN
112.1 LFK :::::
Chan 58

5000
*1600
026°
R-203
191

FL183
*1800
030°
(90)
R-210

FL183
*1900
026°
(138)


SUSHI
023°
(39)
R-203

COLET
023°
(48)
R-203

KYANN
013°
(12)
R-273

HUMBLE
116.6 IAH :::::
Chan 113

DAISETTA
116.9 DAS :::::
Chan 116



SMITH POINT
114.75 MHF :::::
Chan 94(Y)

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

LUFKIN FOUR DEPARTURE

SC-5, 19 MAR 2026 to 16 APR 2026

SC-5, 19 MAR 2026 to 16 APR 2026