

# PHILADELPHIA FOUR DEPARTURE

D-ATIS DEP  
135.925  
CLNC DEL  
118.85 348.6  
CPDLC  
GND CON  
121.9 348.6  
PHILADELPHIA TOWER  
(Rwys 9L/27R, 8/26 and 17/35)  
118.5 327.05  
(Rwy 9R/27L)  
135.1 327.05

RADAR required.

**TOP ALTITUDE:  
ASSIGNED BY ATC**

ALLENTOWN  
117.5 FJC  
Chan 122

POTTSTOWN  
116.5 PTW  
Chan 112

YARDLEY  
108.2 ARD  
Chan 19

**NORTH DEP CON**  
124.35 319.15

SPECIAL INSTRUCTIONS: All aircraft routed via MXE VORTAC, STOEN, PTW VORTAC, FJC VORTAC, ARD VOR/DME, REESY, HAPPS, FOLEZ, HOSKR, MAZIE: departure control frequency 124.35.

MODENA  
113.2 MXE  
Chan 79

FOLEZ  
R-240  
STOEN

ROBBINSVILLE  
113.8 RBV  
Chan 85

HAPPS  
REESY  
R-327

SPECIAL INSTRUCTIONS: All aircraft routed via OOD VORTAC, DITCH, DQO VORTAC, RUUTH, RBV VORTAC, APEER, CHAZR, TEBEE, LULOO, RIDNG: departure control frequency 119.75.


DUPONT  
114.0 DQO  
Chan 87

**SOUTH DEP CON**  
119.75 269.25

COYLE  
113.4 CYN  
Chan 81

WOODSTOWN  
112.8 OOD  
Chan 75

LULOO



CHAZR  
SMYRNA  
111.4 ENO  
Chan 51

**TAKEOFF MINIMUMS**  
Rwy 26: NA-ATC.  
Rwy 27L/R: Standard.  
Rwy 8: Standard with minimum climb of 300'/NM to 1500.  
Rwy 9L: Standard with minimum climb of 280'/NM to 1500.  
Rwy 9R: Standard with minimum climb of 250'/NM to 1500.  
Rwy 17: 300-1 or Standard with minimum climb of 611'/NM to 300.  
Rwy 35: Standard with minimum climb of 280'/NM to 1500.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

NE-4, 19 MAR 2026 to 16 APR 2026

NE-4, 19 MAR 2026 to 16 APR 2026

# PHILADELPHIA FOUR DEPARTURE