

LOC I-BKY 111.5	APP CRS 303°	Rwy Ldg 10679
		TDZE 583
		Apt Elev 617

ILS or LOC RWY 30L


ST LOUIS LAMBERT INTL (STL)

▼ For inop ALS, increase S-ILS 30L Cat E visibility to RVR 4000 and S-LOC 30L Cat A/B visibility to RVR 5500 and cat C/D/E visibility to 1 $\frac{3}{8}$ SM. Simultaneous approach authorized with Rwy 30R requires use of vertical guidance; maintain last assigned altitude until established on glideslope. Simultaneous approach authorized with Rwy 29. LOC only: Rwy 30L helicopter visibility reduction below RVR 4000 NA. *RVR 1800 authorized with use of FD or AP or HUD to DA.




MISSED APPROACH: Climb to 2100 then climbing right turn to 3000 direct STL VORTAC and hold, continue climb-in-hold to 3000.

D-ATIS 125.025 379.925	ST. LOUIS APP CON 132.125 360.6	ST. LOUIS TOWER 118.5 257.7	GND CON 121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	CLNC DEL 119.5 363.1	CPDLC
--	---	---------------------------------------	---	--------------------------------	-------



ELEV 617	D	TDZE 583
----------	----------	----------

Rwy 6-24 7603 X 150
Rwy 11-29 9000 X 150
Rwy 12L-30R 9013 X 150
Rwy 12R-30L 11020 X 150



HIRL all Rwy
TDZ/CL Rwy 11, 12L, 12R, 29, and 30R
FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

	2100	3000	STL					
				TORME INT	JOICE INT STL (19)	FONTI INT STL (22.4)		
				2200	3500	4500		
				4.9 NM	4.6 NM	3.5 NM		
							GS 3.00°	TCH 58
CATEGORY	A	B	C	D	E			
S-ILS 30L*	783/24 200 (200- $\frac{1}{2}$)							
S-LOC 30L	1100/40	517 (500- $\frac{3}{4}$)		1100/55	517 (500-1)			

NC-3, 19 MAR 2026 to 16 APR 2026

NC-3, 19 MAR 2026 to 16 APR 2026