

# ILS or LOC RWY 20

WALLA WALLA RGNL (ALW)

|                           |                        |                 |              |                  |
|---------------------------|------------------------|-----------------|--------------|------------------|
| LOC I-ALW<br><b>111.7</b> | APP CRS<br><b>202°</b> | Rwy Ldg<br>6527 | TDZE<br>1194 | Apt Elev<br>1194 |
|---------------------------|------------------------|-----------------|--------------|------------------|

**DME required.**

**⚠** DME from ALW VOR/DME. Simultaneous reception of I-ALW and ALW VOR/DME required. For inop ALS, increase S-LOC 20 Cat C/D visibility to 2½ SM.

**#** RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Pendleton altimeter setting).

**MALS R**

**MISSED APPROACH:** Climb to 1800 then climbing right turn to 4000 on heading 346° and ALW VOR/DME R-314 to BACUN INT/ALW 15.4 DME and hold.

|                        |  |   |                               |                         |
|------------------------|--|---|-------------------------------|-------------------------|
| ASOS<br><b>135.875</b> | SPOKANE APP CON*<br><b>133.15 379.15</b> | WALLA WALLA TOWER*<br><b>118.5 (CTAF) 289.4</b> | GND CON<br><b>121.6 289.4</b> | UNICOM<br><b>122.95</b> |
|------------------------|--|---|-------------------------------|-------------------------|

