

APCH CRS 005°	Rwy Idg 12,007	TDZE 1347
	Arprt Elev 1372	


(USAF)

MC CONNELL AFB (KIAB)


RNP APCH-GPS	SSALR 	MISSED APPROACH: Climb to 2000 then climbing to 4000, direct PURKE and hold. Expect further clearance from ATC.
<p>▼ * When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1 1/4 miles. ** Circling not authorized west of Rwy 1L-19R.</p>		

D-ATIS 124.65 269.9	WICHITA APP CON 134.8 269.1	TOWER 127.25 291.775	GND CON 118.0 275.8
------------------------	--------------------------------	-------------------------	------------------------

When circling to Rwy 19L at night, operational VGSI required, remain on or above VGSI glidepath until threshold.



RADAR required for holding abv 5000 or abv 230 KIAS.



EMERG SAFE ALT 100 NM 4000

<p>4 NM Holding Pattern</p>	<p>2000 4000 PURKE</p>		ELEV 1372	TDZE 1347	
CATEGORY	A	B	C	D	E
LNAV MDA*	1780/40		433	(500-¾)	
CIRCLING**	1900-1	528 (600-1)	1900-1½ 528 (600-1½)	1940-2 568 (600-2)	2400-3 1028 (1100-3)

