

ILS Z or LOC RWY 18R

LOC I-ALT <u>111.3</u>	APCH CRS <u>175°</u>	Rwy Idg 13,440 TDZE 1378 Arprt Elev 1382	AL-482 [USAF]	ALTUS AFB (KLTS)
----------------------------------	--------------------------------	---	---------------	------------------

DME or RADAR required.

▼ * When ALS inop, increase RVR to 55 and vis to 1 mile.
****** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile;
CAT CDE vis to 1½ miles.

ATIS ★	FORT WORTH CENTER	APP CON	TOWER ★	GND CON	CLNC DEL
109.8 273.5	133.5 350.35	125.1 353.7	119.65 254.4	121.85 275.8	120.65 284.7

***Circling NA W of Rwy 18R-36L.

CAUTION: Autopilot coupled operations NA below 1740 MSL.

EMERG SAFE ALT 100 NM 4900

CATEGORY	A	B	C	D	E
S-ILS 18R	1578/40 200 (200-¾)				
S-LOC 18R *	1760/40 382 (400-¾) 1760/45 382 (400-¾)				
*** CIRCLING	1780-1 398 (400-1)	1840-1 458 (500-1)	1880-1½ 498 (500-1½)	2080-2¼ 698 (700-2¼)	2180-2¾ 798 (800-2¾)
LOCAL ALTIMETER, WITHOUT LAST STEPDOWN FIX					
S-LOC 18R ***	2040/40 662 (700-¾) 2040-1¾ 662 (500-1¾)				
*** CIRCLING	2040-1 658 (700-1)	2040-178 658 (700-178) 2080-2¼ 698 (700-2¼) 2180-2¾ 798 (800-2¾)			

ELEV 1382	TDZE 1378
175° 4.6 NM from FAF ASSAULT STRIP TWR 1496 1524 1516 36L HIRL all Rwy's	176° 3500 x 90 0.45 UP 356° 0.33 DOWN 9001 x 150