

WAAS CH 58299 W01A	APP CRS 006°	Rwy Ldg 6300 TDZE 6431 Apt Elev 6451
--	------------------------	---

RNAV (GPS) X RWY 1

JACKSON HOLE (JAC)

RNP APCH-GPS.	MALS A2	MISSED APPROACH: Climb to 14000 direct QUIRT and on track 088° to DNW VOR/DME and hold, continue climb-in-hold to 14000. *Missed approach requires minimum climb of 385 feet per NM to 7700.
<p>▼ Circling NA east of Rwy 1-19. Baro-VNAV NA.</p> <p>▲ Circling NA for Cat D. Inop table does not apply to LPV, LPV*, LNAV/VNAV, and LNAV Cat C/D.</p> <p>☁ -21°C</p>		

D-ATIS 120.625	SALT LAKE CENTER 133.25 285.6	JACKSON TOWER* 118.075 (CTAF) 1	GND CON 124.55	UNICOM 122.95
--------------------------	---	---	--------------------------	-------------------------



<p>ELEV 6451</p> <p>CL Rwy 1-19</p> <p>HIRL Rwy 1-19</p>		<p>TDZE 6431</p>		
<p>7 NM Holding Pattern</p> <p>17500 ← 186°</p> <p>11700 → 006°</p> <p>GP 3.00°</p> <p>TCH 50</p>		<p>14000</p> <p>QUIRT</p> <p>Ir 088°</p> <p>DNW</p>		
<p>HOMVA</p> <p>VALCU</p> <p>DECEV</p> <p>ZUGEN</p> <p>COVGI</p> <p>RW01</p>		<p>3.4 NM to RW01</p> <p>2.1 NM</p> <p>3.4</p>		
CATEGORY	A	B	C	D
LPV DA*		6651/40	220 (200-¾)	
LPV DA		7445-4	1014 (1000-4)	
LNAV/VNAV DA		7327-4	896 (900-4)	
LNAV MDA	7540/55 1109 (1100-1)	7540-1½ 1109 (1100-1½)	7540-3 1109 (1100-3)	
CIRCLING	7540-1½ 1089 (1100-1½)	7540-1½ 1089 (1100-1½)	7560-3 1109 (1200-3)	NA

NW-1, 19 MAR 2026 to 16 APR 2026

NW-1, 19 MAR 2026 to 16 APR 2026