

# PALMS FOUR DEPARTURE

AL-556 (FAA)

RADAR required.

**TOP ALTITUDE:  
ASSIGNED BY ATC**

AUSTIN DEP CON  
 127.225 317.65  
 D-ATIS  
 124.4  
 CLNC DEL  
 125.5 263.0  
 CPDLC  
 GND CON  
 121.9 348.6  
 AUSTIN TOWER  
 121.0 281.5

CENTEX  
 112.8 CWK  
 Chan 75

STINSON  
 108.4 SSF  
 Chan 75

R-090

PALMS  
5000

R-352


CORPUS CHRISTI  
 115.5 CRP  
 Chan 102



### TAKEOFF MINIMUMS

Rwys 18L/R: Standard.

Rwys 36L/R: Standard with minimum climb of 240' per NM to 2600.



NOTE: Chart not to scale.



### DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 18L/R, 36L/R: Climb on assigned heading for vectors to CWK VORTAC, then on CWK R-169 to cross PALMS INT at or above 5000, then on CRP R-352 to CRP VORTAC. Maintain ATC assigned altitude, expect filed altitude 10 minutes after departure.

# PALMS FOUR DEPARTURE