

WAAS CH 77519 W04A	APP CRS 044°	Rwy Ldg 11010 TDZE 13 Apt Elev 13
--	------------------------	--

RNAV (GPS) Y RWY 4L


JOHN F KENNEDY INTL (JFK)

RNP APCH.

Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C.

MISSED APPROACH: (Do not exceed 210K until BARJR) Climb to 3000 direct BARJR and track 067° to DUFFY and hold.


D-ATIS (NE) 117.7	NEW YORK APP CON 128.125 269.0	KENNEDY TOWER (4R/22L and 13L/31R) (4L/22R and 13R/31L) 119.1 281.55 123.9 281.55	GND CON 121.9 348.6
-----------------------------	--	---	-------------------------------



NE-2, 19 MAR 2026 to 16 APR 2026

NE-2, 19 MAR 2026 to 16 APR 2026

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).



CATEGORY	A	B	C	D
LPV DA		232/40	219 (300-3/4)	
LNAV/VNAV DA		329/50	316 (400-1)	
LNAV MDA	480/55	467 (500-1)	480-1 3/8	467 (500-1 3/8)
CIRCLING	640-1	627 (700-1)	680-1 3/4	680-2
			667 (700-1 3/4)	667 (700-2)

