

WAAS CH 72830 W36A	APP CRS 358°	Rwy Ldg TDZE Apt Elev	5759 36 36
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 36R


VALLEY INTL (HRL)

RNP APCH - GPS.


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C or above 54°C. Baro-VNAV and VDP NA when using Port Isabel altimeter setting. When local altimeter setting not received, use Port Isabel altimeter setting: increase LPV DA to 278 feet; increase LNAV/VNAV DA to 328 feet and all visibilities ½ SM, increase all MDAs 60 feet and LNAV visibility Cat C and D ½ SM, and Circling visibility Cats C and D ¼ SM.

MISSED APPROACH:
Climb to 2000 direct BETVE and hold.

ATIS 124.85	VALLEY APP CON 120.7 279.5	HARLINGEN TOWER ★ 119.3 (CTAF) 317.6	GND CON 121.7	UNICOM 122.95
-----------------------	--------------------------------------	--	-------------------------	-------------------------



ELEV 36	D	TDZE 36
---------	----------	---------



2000	BETVE	AYUNA 2.5 NM to RW36R	YOTLU 1500	ZABIT 2000
		1 NM to RW36R	880	1500
		1 NM	1.5 NM	2 NM
			7 NM	
				GP 3.00° TCH 55
CATEGORY	A	B	C	D
LPV DA		236-¾	200 (200-¾)	
LNAV/VNAV DA		286-¾	250 (300-¾)	
LNAV MDA		400-1	364 (400-1)	
CIRCLING	460-1 424 (500-1)	560-1 524 (600-1)	600-1½ 564 (600-1½)	680-2 644 (700-2)

SC-3, 19 MAR 2026 to 16 APR 2026

SC-3, 19 MAR 2026 to 16 APR 2026