

LOC I-MIV 110.9	APP CRS 100°	Rwy Idg TDZE Apt Elev	6003 74 85
---------------------------	------------------------	-----------------------------	---------------------------------------

ILS or LOC RWY 10

MILLVILLE MUNI (MIV)

⚠ Inoperative table does not apply. Rwy 10 helicopter visibility reduction below 3/4 SM NA. When local altimeter setting not received, use Atlantic City altimeter setting: increase DA to 407 feet; increase all MDAs 60 feet and visibility Cat B 1/2 SM and Cats C and D 1/2 SM. Autopilot coupled approach NA below 300 MSL.


MALSR 

MISSED APPROACH: Climb to 550 then climbing left turn to 2000 direct VCN VOR/DME and hold.

ASOS
119.6

ATLANTIC CITY APP CON
124.6 327.125



UNICOM
123.0 (CTAF) 



NE-2, 19 MAR 2026 to 16 APR 2026

NE-2, 19 MAR 2026 to 16 APR 2026

ELEV 85	TDZE 74
---------	---------



CATEGORY	A	B	C	D
S-ILS 10	347-1 273 (300-1)			
S-LOC 10	980-1 1/4	906 (900-1 1/4)	980-2 1/2	906 (900-2 1/2)
CIRCLING	980-1 1/4	895 (900-1 1/4)	980-2 3/4 895 (900-2 3/4)	980-3 895 (900-3)
XECRE FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)				
S-LOC 10	440-1 366 (400-1)			
CIRCLING	520-1 435 (500-1)	580-1 495 (500-1)	660-1 1/2 575 (600-1 1/2)	660-2 575 (600-2)

MIRL Rwy 10-28 and 14-32 

FAC to MAP 5.4 NM

Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48