

WAAS CH 87112 W35A	APP CRS 357°	Rwy Ldg TDZE 790 Apt Elev 794	8501
--	------------------------	---	-------------

RNAV (GPS) RWY 35

GERALD R FORD INTL (G.R.R)

RNP APCH - GPS.

RADAR required for procedure entry.


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV Cat D visibility to RVR 6000. * RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSRL




MISSED APPROACH: Climb to 3000 direct HABKO and on track 352° to CLOCK and hold.

ATIS 118.725	GREAT LAKES APP CON* 128.4 257.6	GRAND RAPIDS TOWER* 135.65 (CTAF) 339.8	GND CON 121.8	UNICOM 122.95
------------------------	--	--	-------------------------	-------------------------



ELEV 794	D	TDZE 790
----------	----------	----------



3000	HABKO	CLOCK	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 74).	
↑	tr 352°		JJUDD	
	HONSE 2 NM to RW35	FALSU 2500	3000	GP 3.00° TCH 55
	1 NM to RW35	2500	3000	
	1480	2500	3000	
	1 NM	3.1 NM	6.1 NM	
CATEGORY	A	B	C	D
LPV DA*	990/24 200 (200-½)			
LNAV/VNAV DA	1236/50 446 (500-1)			
LNAV MDA	1180/24 390 (400-½)	1180/35 390 (400-¾)	1180/50 390 (400-1)	
CIRCLING	1260-1 466 (500-1)	1340-1½ 546 (600-1½)	1360-2 566 (600-2)	

EC-1, 19 MAR 2026 to 16 APR 2026

EC-1, 19 MAR 2026 to 16 APR 2026