

MAYNR THREE DEPARTURE (RNAV)

**TOP ALTITUDE:
ASSIGNED BY ATC**



RNAV 1 - DME/DME/IRU or GPS.

From SLIPT to MAXIM: RNAV 1 - GPS.

From SLIPT to CANOA: RNAV 1 - GPS.

RADAR required for non-GPS equipped aircraft.

RADAR required.

TAKEOFF MINIMUMS

Rwy 9L: Standard with minimum climb of 500'/NM to 1300.

Rwy 9R: Standard with minimum climb of 500'/NM to 1500.

Rwy 13: Standard with minimum climb of 500'/NM to 1800.

Rwy 27L: Standard with minimum climb of 500' /NM to 1900.

Rwy 27R: Standard with minimum climb of 500'/NM to 1700.

Rwy 31: Standard with minimum climb of 500'/NM to 1400.

NOTE: Jet aircraft only.

NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.

MSA MB 25 NM

291

MIAMI DEP CON

125.5 354.1

ATIS

124.C

CLINC DEL

133.0

GND CON

121.7

MIAMI EXEC TOWER★

118.9 (CTAF)

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SE-3, 19 MAR 2026 to 16 APR 2026

MAYNR THREE DEPARTURE (RNAV)

(MAYNR3.MAYNR) 31OCT24

MIAMI, FLORIDA
MIAMI EXEC (TMB)

