



WAAS CH 66028 W27A	APP CRS 274°	Rwy Ldg TDZE 777 Apt Elev 781
--	------------------------	---


RNAV (GPS) RWY 27

FULTON COUNTY (USE)

RNP APCH - GPS.		MISSED APPROACH: Climb to 3000 direct DUCZZ and hold.
▼ Rwy 27 helicopter visibility reduction below ¾ SM NA. ▲ Circling NA to Rwys 18 and 36. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Circling Rwy 9 NA at night.		

AWOS-3P 127.375	TOLEDO APP CON 134.35 317.55	UNICOM 123.0 (CTAF) 0
---------------------------	--	---------------------------------



3000 ↑	DUCZZ 	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 33).				4 NM Holding Pattern
						
RW27		1.6 NM	3.5 NM	5 NM		
CATEGORY	A	B	C	D		
LPV DA	1092-1 315 (400-1)					
LNAV/ VNAV DA	1095-1 318 (400-1)					
LNAV MDA	1180-1	403 (400-1)	1180-1½		403 (400-1½)	
CIRCLING	1280-1	499 (500-1)	1480-2 699 (700-2)		1480-2¼ 699 (700-2¼)	

EC-2, 19 MAR 2026 to 16 APR 2026

EC-2, 19 MAR 2026 to 16 APR 2026