

RADAR INSTRUMENT APPROACH MINIMUMS

FALLON NAS (VAN VOORHIS FLD) (KNFL)

Fallon, NV Amdt 6 02OCT25 (25275) (USN)

ELEV 3935

RADAR¹ - (E) 120.85x 121.875x 257.65x 277.4x 308.4x 346.4x 360.2x **T**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	7	3.0°/50/931	ABCDE	4130 -¾	200	(200-¾)
	13L	3.0°/50/954	ABCDE	4135 -¾	200	(200-¾)
	13R	3.0°/50/958	ABCDE	4135 -¾	200	(200-¾)
	31L ²	3.5°/57/934	ABCDE	4197 -⅞	270	(300-⅞)
	31R	3.5°/57/925	ABCDE	4198 -⅞	270	(300-⅞)
ASR	31L ³		ABCDE	4280 -1	353	(400-1)
	31R ⁴		ABCDE	4300 -1	372	(400-1)
	13L ⁵		AB	4380 -1	445	(500-1)
			CDE	4380 -1½	445	(500-1½)
	13R ⁶		AB	4380 -1	445	(500-1)
			CDE	4380 -1½	445	(500-1½)
CIR	13L/R, 31L/R		A	4400 -1	465	(500-1)
			B	4440 -1	505	(600-1)
			C	4780 -2½	845	(900-2½)
			D	5120 -3	1185	(1200-3)
			E	5160 -3	1225	(1300-3)
		7		AB	4400 -1	505
		C	4780 -2½	845	(900-2½)	
		D	5120 -3	1185	(1200-3)	
		E	5160 -3	1225	(1300-3)	

CAUTION: ATC Missed Approach Minimum Climb Rate to 6500

PAR/ASR	Rwy	Knots	60	120	180	240	300	360
	7	FPM	370	740	1110	1480	1850	2220
	13L/R	FPM	300	600	900	1200	1500	1800

¹No-NOTAM MP sked: PAR-2200-0000Z++ Thu, ASR-1500-1700Z++ Wed, when ceil-vis 3000-5 and above.

²VGSI and PAR glidepath not coincident (VGSI Angle 3.50/TCH 61).

³Step Down Fix 3 NM 4980'.

⁴Step Down Fix 3 NM 4940'.

⁵Step Down Fix 3 NM 4960'.

⁶Step Down Fix 2 NM 4600'.

CAUTION: Fallon Muni Airport (uncontrolled) 5 NM NW pattern altitude 800' AGL.

19 MAR 2026 to 16 APR 2026

19 MAR 2026 to 16 APR 2026

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

26022

N2

RADAR INSTRUMENT APPROACH MINIMUMS

YUMA MCAS/YUMA INTL (KNYL)

Yuma, AZ Amdt 2 22JAN26 (26022) (USN)

ELEV 213

RADAR - (E) 120.9x 124.15x 125.55x 125.95x 254.0x 270.8x 278.7x 286.0x 301.2x 305.2x



	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAT^h/ HAA</u>	<u>CEIL-VIS</u>
PAR	21R ¹	3.0°/54/1073	ABCDE	393-½	200	(200-½)
	3L	3.0°/54/1021	ABCDE	395-¾	200	(200-¾)
PAR W/O GS	21R ²		AB	600-½	407	(400-½)
			CDE	600-¾	407	(400-¾)
	3L		AB	640-1	445	(500-1)
			CDE	640-1½	445	(500-1½)
ASR	21R ³		AB	620-½	427	(500-½)
			CDE	620-¾	427	(500-¾)
	3R		AB	600-1	412	(400-1)
			CDE	600-1½	412	(400-1½)
	21L		AB	620-1	412	(500-1)
			CDE	620-1½	412	(500-1½)
	3L		AB	640-1	445	(500-1)
			CDE	640-1½	445	(500-1½)
CIR	ALL RWY		A	680-1	467	(500-1)
			B	860-1¾	647	(700-1¾)
			C	860-2	647	(700-2)
			DE	860-2¼	647	(700-2¼)

¹When ALS inop, increase vis to ¾ mile. TCH (54) not coincident with VGSI TCH (50).

²When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1½ miles.

³When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1¼ miles.

19 MAR 2026 to 16 APR 2026

19 MAR 2026 to 16 APR 2026

SW-4

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

26022

N2