

ALAMO FIVE DEPARTURE

RADAR required.

**TOP ALTITUDE:
ASSIGNED BY ATC**

SAN ANTONIO DEP CON
125.7 290.225
ATIS
128.8
CLNC DEL (When twr closed)
121.7
GND CON
121.7 379.9
STINSON TOWER ★
118.2 (CTAF) 379.9

BROWNWOOD
113.55 BWD
Chan 82(Y)

COWBOY
116.2 CVE
Chan 109

GOOCH SPRINGS
112.5 AGJ
Chan 72



CENTEX
112.8 CWK
Chan 75

STONEWALL
113.8 STV
Chan 85

NOTE: GOBBY Transition: Right turn at GOBBY NA for aircraft required FL240 and above.
NOTE: HENLY Transition: Right turn at HENLY NA for aircraft required FL240 and above.

TAKEOFF MINIMUMS

- Rwy 10: Standard with minimum climb of 230'/NM to 1900.
- Rwy 14: Standard with minimum climb of 220'/NM to 1900.
- Rwy 28: 300-1½ or standard with minimum climb of 230'/NM to 900, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1800' prior to DER.
- Rwy 32: Standard with minimum climb of 230'/NM to 1700.



NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SC-3, 16 APR 2026 to 14 MAY 2026

SC-3, 16 APR 2026 to 14 MAY 2026