ILS or LOC RWY 13

SAN MARCOS RGNL (HYI)

LOC I-RUM	APP CRS	Rwy Ldg	5601
108.7	126°	TDZE	593
		Apt Elev	595

ADF required.

T NA Circling NA for Cat E southwest of Rwy 13-31. Inop table does not apply to S-ILS 13 all Cats. For inop ALS, increase S-LOC 13 Cat C/D/E visibility to 1⅞ SM.

MALS

MISSED APPROACH: Climb to 2000 then climbing left turn to 3200 direct GARYS LOM/INT and hold.

ATIS	AUSTIN APP CON	SAN MARCOS TOWER ★	GND CON
120.825	119.0 370.85	126.825 (CTAF) L	120.125

ALTERNATE MISSED APCH FIX

113.8 STV Chan 85 R-040 105° 285° R-105 BETTI STV 36.8 116.8 SAT Chan 115

CENTEX 112.8 CWK Chan 75

Procedure NA for arrival on CWK VORTAC airway radials 222 CW 271.

3700 215° (33.3)

351° 171° 306° 126° 306° R-215 R-105 R-040

113.8 STV Chan 85

MSA RU 25 NM 3100

BETTI STV 36.8

LOM/IAF GARYS 272 RU GARYS INT

1009±

LOCALIZER 108.7 I-RUM

3500 047° (32.7)

Procedure NA for arrival on SAT VORTAC airway radials 002 CW 081.

116.8 SAT Chan 115

SAN ANTONIO 116.8 SAT Chan 115

Remain within 15 NM

RU LOM GARYS INT

306° 126° 2441 3200 2700

GS 3.00° TCH 57

5.5 NM

2000 3200 RU

ELEV 595 TDZE 593

126° 13 17 35 26 8 5601 X 100 6330 X 100 5214 X 100 0.4% UP 0.4% UP TWR

CATEGORY	A	B	C	D	E
S-ILS-13	793-¾ 200 (200-¾)				
S-LOC-13	1260-¾ 667 (700-¾)		1260-1¾ 667 (700-1¾)		
CIRCLING	1260-1 665 (700-1)		1260-1⅞ 665 (700-1⅞)	1320-2¼ 725 (800-2¼)	1340-2¾ 745 (800-2¾)

MIRL Rwys 8-26, 13-31, and 17-35 L

FAF to MAP 5.5 NM

Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

SC-3, 16 APR 2026 to 14 MAY 2026

SC-3, 16 APR 2026 to 14 MAY 2026