

VOR/DME RDD 114.35 Chan 90(Y)	APP CRS 355°	Rwy Ldg 6997 TDZE 499 Apt Elev 505
--	------------------------	---

VOR RWY 34


REDDING RGNL (RDD)

⚠ Inop table does not apply to S-34 Cats C/D. MACHL fix minimums: for inop ALS, increase S-34 Cat C/D visibility to 1 3/4 SM.

MALS 

MISSED APPROACH: Climb to 2100 then climbing right turn to 5300 on heading 090° and on RDD VOR/DME R-044 to ITMOR INT and hold, continue climb-in-hold to 5300.


ATIS 124.1	OAKLAND CENTER 132.2 350.3	REDDING TOWER ★ 119.8(CTAF) 269.25	GND CON 121.7	UNICOM 122.95
----------------------	--------------------------------------	---	-------------------------	-------------------------



CATEGORY	A	B	C	D
S-34	1680-3/4 1181 (1200-3/4)	1680-1 1181 (1200-1)	1680-3	1181 (1200-3)
CIRCLING	1680-1 1/4 1175 (1200-1 1/4)	1680-1 1/2 1175 (1200-1 1/2)	1680-3	1175 (1200-3)

MACHL FIX MINIMUMS

S-34	1100-1/2	601 (600-1/2)	1100-1 3/8	601 (600-1 3/8)
CIRCLING	1100-1	595 (600-1)	1120-1 3/4 615 (700-1 3/4)	1340-2 3/4 835 (900-2 3/4)



SW-2, 16 APR 2026 to 14 MAY 2026

SW-2, 16 APR 2026 to 14 MAY 2026